

# Firestair Light

Innovative new Australian made LED design for fire stair, carpark and service areas. The market leader in batten lights.

**Prolume's patented 3<sup>rd</sup> Generation LED Firestair light offers an innovative slim-line solution for replacing existing fluorescent lighting.**

The Prolume Carpark light is a slim-line LED luminaire specifically designed to maximise light output and energy efficiency whilst minimising maintenance costs for Australian car parking, back of house and fire stair environments.

The precision moulded opal impact resistant polycarbonate lens provides a distribution designed to maximise lighting on both horizontal and vertical surfaces whilst achieving consistent light output in a stylish package.

*Up to **90%** energy savings  
over conventional technologies*

With microwave sensing option, the light uses a minimal 6w in standby mode, microwave sensors detect motion within an 8m radius to further activate the LEDs to provide full illumination at 17w for a predefined period.

The innovative design allows for rapid installation via unique slide-fix method and quick-connect plug system. Effortless maintenance and/or upgrades.

## Options

- Available in 600, 900, 1200 & 1500mm\* lengths
- Motion Sensor (Concealed)
- Dimmable Ballasts DSI/DALI
- Light output 4000K/5500K
- Emergency models with battery back up

*\*Special order only*



## Applications

- Car parking stations
- Fire stairs
- Schools
- Service areas
- Shopping centres
- Hospitals

## Key Benefits

- Australian designed and manufactured to ensure build quality – patented Prolume design
- Up to 90% energy savings over conventional technologies
- Matches footprint of standard fluorescent lights
  - No need to paint exposed ceilings
  - No need to extend conduits
- Readily accepts Pyro cables
- Significant maintenance savings
- Available with or without motion sensors and/or backup batteries for installation in premises with integrated building management systems

## Product Details

600mm/1200mm Light	6W Standby, 17W Full
Sensor Range	8 m (option)
Sensor Timing	10 sec – 20 mins
Back up Battery	120 mins at Full
Luminosity standby	400 lm
Luminosity full	1900 lm
AC input	220 - 240V
Operating Temp	-40C - +80C
Warranty body	10 years
Warranty elect.	5 years
Dimensions	1230 L X 120 W X 85 H 630 L X 120 W X 85 H
Colour	4000K, 5500K

*Compliant with Australian product safety standards.*